

AVANTE

ELEVATE
YOUR SOUND



AS8 ACTIVE LINE ARRAY PA SYSTEM

Amplifier

Inputs	2xXLR/TRS Combo's, Stereo 1/8" inputs, dual 1/4" inputs, Bluetooth®
Outputs	XLR balanced line output
Power output	RMS 250W RMS, 1000W peak
Volume	Input Gain control per channel
EQ	Main out 2 band shelving EQ
LEDs	Power/Limiter indicator
Power Input	100-240V~50/60Hz switchable 250W
Amplifier	Class D amplifier with switching power design

Satellite

Passive full-range speaker


Frequency response	180-20kHz
Max. output SPL	120dB
Impedance	4ohms
Driver	6x2.75" full range line array
Cabinet	ABS plastic
Grill	1.0mm steel
MEAS/G.W.	51x44x48CM/1PC/13.3KG (SUB)

Subwoofer

Active vented subwoofer

Frequency Response	55-200Hz
Max output SPL	116dB (at max. amp output)
Impedance	4 Ohm
Driver	8" subwoofer, 1.5" vc 28Oz
Cabinet	PP plastic
Grill	1.0mm steel
Listings	FCC, CE, & ETL

SPL vs Freq



Map 27: AS8-SPL-3M-MIC1.8-0.1V

www.avanteaudio.com

